




Egret ® Spooled foam Tap

EGSF-2

SECTION 1: DESCRIPTION & BENEFITS

- 2mm high-density closed-cell PE foam as carrier
- Coated with double sided very high tack adhesive
- Laminated with red or green PET liner
- Excellent properties of sound dampening, cushioning
- Touch feeling like wax, odorless, non-toxic
- Plastic or paper core is available
- Stable chemical properties, good corrosion resistance
- Can be spooled in a single extra-long reel of thousands of meters



SECTION 2: SPECIFICATIONS

Product Characteristics	Performance Data	Test Method
Carrier Color	White/Black	Visual
Liner Color	Red/Greem	Visual
Density	≥ 30 KG/m ³	ASTM D-3575
Peel Adhesion	≥ 5 N/CM	ASTM D-3330
Loop Tack	16 # steel ball	GB/T 4852-84
Tensile strength	16 N/CM	ASTM D3759
Elongation	≥ 130%	ASTM D-3330
Reel Length	2000 meters	

SECTION 3: APPLICATIONS & OTHER DETAILS

- Automotive interior fixing parts
- Home appliance sound dampening
- Life-saving and buoyant material
- Building material sealing
- Thermal insulation material



Sliced roll width available (or customized): 5mm-100mm

Standard Length: 1000m-5000m bobbin/spool/reel

Tolerance: Thickness: +/- 10% Width: +/-1.0mm Length: +/- 0.4m

Storage: Indoor storage: -5°C-40°C(humidity:<80%), cool & dry, free of direct sunlight

Shelf Life: 12 months in room temp.

N.B. Please keep the operating surface clean, dry, and free of grease or other dirt & dust. So that **Egret Tape** can have a best performance.

Changzhou Egret Manufacturing Co., Ltd

No.4, Tongshun Rd, Henglin Town, Changzhou 213101 • China

T: +86 519 8878 9969 Ext. 807 Email: info@egretmfg.com Website: www.egretmfg.com